



11 Hours of Battery Life

(Micro-B USB type)



Float'n Flash



Optional Speaker-Microphone, HM-213



*For illustration purpose only

<u>IC-M25EURC</u>

FEATURES

Slim, Lightweight, **High Performance**

The IC-M25EURO has the slimmest (depth: 30.5mm) and lightest (220g) body as a floating marine transceiver*. It also delivers uncompromised performance that will exceed expectations.

*As of July, 2015, researched by Icom.

Large LCD, **Simple User Interface**

The IC-M25EURO's LCD is 30% larger than its predecessor, the IC-M23 and shows clearly large channel number and status icons. The buttons on the front panel are well laid out and provide simple and straightforward operation.

USB Charging (Micro-B USB type)

A standard USB connector (Micro-B type) is used for charging the IC-M25EURO. Cigarette lighter cables or mobile batteries for charging smartphones or other devices can be used with the IC-M25EURO*.

* The IC-M25EURO accepts 5V/1A (Max.) input. Use of third-party products is not guaranteed.

Float'n Flash

The IC-M25EURO floats and lets you know where it is with the flashing red LED light and LCD/key backlight.

11 Hours of Battery Life

The built-in 1500mAh lithium-ion battery allows 11 hours (approx.) of long operation*.

* Typical operation with Tx (Hi): Rx: standby=5:5:90

Optional Speaker-Microphone, HM-213

The optional waterproof speaker-microphone, HM-213, provides commercial grade convenience while mounting the radio around the waist. The radio floats even when the HM-213 is attached.

550mW Audio Output

The IC-M25EURO provides a powerful 550mW (typical) audio output and received voice can be heard loud and clear.

Other Features

- IPX7 waterproof construction (1m depth of water for 30 minutes)
- · 4-step battery life indicator
- Dual/Tri-watch functions*
- Instant access to Ch 16 or programmable call channel
- Favorite channel function
- · Monitor function opens noise squelch
- Auto scan function*
- · LCD auto backlighting
- AquaQuake[™] draining function
- * Not available in the HOL version.

SPECIFICATIONS

GENERAL	
Frequency range Tx	156.000-161.450MHz
Rx	156.000-163.425MHz
HOL version Tx	156.000-161.600MHz
Rx	156.000-163.425MHz
Usable channel groups	INT, USA*, ATIS* channels
Coable charmer groups	* Depending on version
Type of emission	16K0G3E (FM)
Power supply voltage	3.7V DC nominal
Current drain (at 3.7V DC)	
Tx	2.3A
Rx (Internal SP/External SP)	
Operating temperature range	-15°C to +55°C
Antenna impedance	50
Dimensions (W×H×D) (projec-	56.6×134.2×30.5mm
tions not included)	30.0x 134.2x30.311111
Weight (approximately)	220g
vvcigitt (approximately)	
3 ,,	(With FA-SC59V and MB-133)
TRANSMITTER	(With FA-SC59V and MB-133)
	5W (approx.)/1W/0.5W*
TRANSMITTER Output power	
	5W (approx.)/1W/0.5W*
Output power	5W (approx.)/1W/0.5W* * For only FRG version
Output power Max. frequency deviation	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz
Output power Max. frequency deviation Frequency stability	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz
Output power Max. frequency deviation Frequency stability Spurious emissions	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power	5W (approx.)/1W/0.5W* *For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation	5W (approx.)/1W/0.5W* *For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity Squelch sensitivity	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD) -6dBµ emf typ. (at threshold)
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity Squelch sensitivity Adjacent channel selectivity	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD) -6dBµ emf typ. (at threshold) 70dB
Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity Squelch sensitivity Adjacent channel selectivity Spurious response	5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD) -6dBµ emf typ. (at threshold) 70dB 70dB

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation

Applicable IP Rating

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

OPTIONS Some options may not be available in some countries. Please ask your dealer for details.













The "3D GENUINE Icom label" is attached to the rear panel Check the Icom website for details: http://www.icom.co.jp/world/genuine-info

Icom, Icom Inc. and Icom Iogo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

ICOM Inc. 1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302

Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

12421 Willows Road NE, Kirkland, WA 98034, U.S.A. Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com URL: http://www.icomamerica.com

Icom Canada

Glenwood Centre #150-6165 Highway 17A, Delta, B.C., V4K 5B8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-0 Fax: +49 (6196) 76685-50 -mail: info@icomeurope.cor URL: http://www.icomeurope.com

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" Bajos A 08174, Sant Cugat del Valles, Barcelona, Spain Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46 E-mail: icom@icomspain.com URL: http://www.icomspain.com

Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00 URL: http://www.icom-france.com

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road, Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505 E-mail: sales@icom.net.au URL: http://www.icom.net.au

Icom New Zealand

39C Rennie Drive, Airport Oaks, Auckland, New Zealand Phone: +64 (09) 274 4062 Fax: +64 (09) 274 4708 E-mail: inquiries@icom.co.nz URL: http://www.icom.co.nz

Asia Icom Inc.

Fax: +886 (02) 2559 1874 E-mail: sales @ asia-icom.com URL: http://www.asia-icom.com

Your local distributor/dealer: