

Further Advanced Dualwatch Remote Control Software




Shows MAIN and SUB controls
Click the indicator to change the settings


RIT tuning knob and ΔTX functions added

[MUTE] button added

SUB dial added



MAIN spectrum scope



SUB spectrum scope

Dualwatch, Dual Spectrum Scope Control

The dualwatch operation and dual spectrum scopes with the waterfall functions* can be used on your remote PC. MAIN and SUB spectrum scopes can be observed on the RS-BA1 at the same time. Of course, the RS-BA1 can be used with Icom single receiver transceivers.

* The dualwatch and dual spectrum scope functions are only for the IC-7851, IC-7850 and IC-7610. The spectrum scope functions (single receive) are usable with the IC-7300, IC-9700 and IC-705.

Most Functions Can Be Controlled


Most functions and modes of your transceiver, including interference rejection functions and IF filter settings, can be controlled using the CI-V commands. The following functions are added to the RS-BA1 Version 2.

- Panel size can be enlarged (Normal or large size selectable)
- Indicator click operation to change the settings
- RIT and ΔTX functions
- [MUTE] button
- SUB dial

Low Latency, High Quality Audio Over an IP Network

The RS-BA1 offers real-time operation with low latency, high quality audio. You can use the transceiver installed in another room using your home network, or even from a remote location over the Internet*.

* A static public IP address or Dynamic DNS is required for the base station (Server) PC, when you configure the remote control system through the Internet.



FUNCTION COMPATIBILITY CHART

| | IC-7851 IC-7850 | IC-7800 IC-7700 | IC-7610 | IC-7600 | IC-7410 IC-9100 | IC-7300 | IC-7200 | IC-7100 | IC-9700 | IC-705 |
|------------------------------|--------------------|--------------------|---------|---------|--------------------|---------|---------|---------|---------|--------|
| Dualwatch Function | ✓ | – | ✓ | – | – | – | – | – | – | – |
| Server Function | ✓ | ✓ | ✓ | – | – | – | – | – | ✓ | ✓ |
| Remote Power ON/OFF | ✓ | ✓ | ✓ | ✓ | – | ✓ | – | ✓ | ✓ | ✓ |
| Spectrum Waterfall Scope | ✓ | – | ✓ | – | – | ✓ | – | – | ✓ | ✓ |
| APF AF Level Adjustment | ✓ | ✓ | ✓ | ✓ | – | – | – | – | – | – |
| CW Keyer | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | – | ✓ | ✓ | ✓ |
| Voice Recording/Playback | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| USB Dial with Optional RC-28 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

* Depending on your transceiver, some functions or modes cannot be used, or you need to update the transceiver's firmware. Use the latest firmware version for your transceiver.

MINIMUM SYSTEM REQUIREMENTS

PC (Base server station or Remote station)

* When only one transceiver and one PC are connected to the Server PC.

| | |
|------------------------|--|
| Operating System | Windows® 10 (32/64 bit), Windows® 8.1 (32/64 bit) (Except for Windows® RT), |
| CPU | 1.8 GHz Processor or better |
| Memory | Windows® 10 (32 bit): 2 GB or more, Windows® 10 (64 bit): 4 GB or more, Windows® 8.1 (32 bit): 2 GB or more, Windows® 8.1 (64 bit): 4 GB or more, |
| Hard disk space | 150 MB or more of available disk space *The Voice Memory or Recording function will require more space. |
| Network data speed | To use the Dualwatch function (IC-7851/7850/7610) |
| For the Base station | Upload: 1.2 Mbps Download: 350 kbps, or faster |
| For the Remote station | Upload: 350 kbps Download: 1.2 Mbps, or faster |
| | Other models (Other than the IC-7851/7850/7610) |
| For the Base station | Upload: 500 kbps Download: 350 kbps, or faster |
| For the Remote station | Upload: 350 kbps Download: 500 kbps, or faster |
| | (When the default audio quality is used) |
| Display resolution | 1024 × 768 pixels (enlargeable) |
| Other | Speaker and microphone or headset (purchase separately) On-board sound chipset recommended |

OPTIONAL ACCESSORY

RC-28 USB Remote Encoder



- Adjustable dial sensitivity and auto tuning step (OFF/Low/High)
- Two programmable keys of four functions (Push/Hold down)
- Large PTT switch (Push to toggle/Hold down to transmit)
- The RC-28 will still operate in the background even if a different application (Such as logging software) is open



Operation image

RS-BA1 SUPPLIED ITEMS

- CD (including the RS-BA1 instruction manual, the RS-BA1 installer, the USB driver and the USB driver installation guide)
- USB cable (A-B type)
- Installation guides

Note for original version RS-BA1 users: Free upgrade service from RS-BA1 to RS-BA1 Version 2 is not available. To obtain the new features in the RS-BA1 Version 2, the purchase of a new software package is required.

All stated features, screen shots, and specifications may be subject to change without notice or obligation. Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icomjapan.com

Count on us!

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom Asia Co., Ltd.
www.icomasia.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Shanghai Icom Ltd.
www.bjicom.com

Icom France s.a.s.
www.icom-france.com