



VHF MARINE TRANSCEIVER
IC-M430E

Compact, Stylish and Packed with Features



A New Generation of Stylish and Compact Communication



Designed for Marine Duty

25 W RF Output with Class D DSC

For safety on the water, the IC-M430E offers 25 watts of transmit power. It provides built-in Class D DSC functionality for the distress calling button and direct calling.

Slimmer Body Fits in Tight Spaces

The compact 202 x 82 x 52.6 mm body provides exceptional installation flexibility. The slim depth profile enables installation in limited spaces while maintaining ample clearance behind the radio for proper cable management.

Simplified Flush Mounting

The radio features MFD-style mounting for elegant installation. Screw the radio directly into place, and snap-on body covers hide all mounting hardware for a clean finish. This mounting method is ideal for side pod installations on center console hard tops.




Enhanced Visibility

Three Display Modes for Comfortable Operation

First* colour display in class. The wide viewing angle and bright screen deliver exceptional readability in any environment. Choose from Light mode, Dark mode, or Night mode; whether operating in direct sunlight or complete darkness, the display remains clearly visible. Seamlessly switch between Day and Night modes with a one-touch button. Backlit operation keys ensure confident operation in the dark.

* According to Icom research as of September 2026.



Expand Your Onboard System

Remote Microphone Installation Options

The included hand microphone can be mounted directly to the front panel or rear-mounted using the extension cable OPC-1000*. For dual-station capability, the CommandMic™* provides full remote control from a second location (cable extension up to 60 ft/18.3 m) and supports intercom functionality between stations. Ideal for sailboat installations requiring a second control position at the helm. A 90° L-type adapter* is a useful addition that helps prevent connector damage.

* Optional accessory



Installation example (HM-205RB + OPC2522L + OPC-1000)

Flexible System Integration

The radio offers plug-and-play installation via the NMEA 2000™, and also supports NMEA 0183-HS network, enabling data sharing between the radio and other marine electronics. Compatible with Icom MA-510TR, and you can transmit an Individual DSC call to a selected AIS target.

Built-in GNSS (GPS) Antenna

The IC-M430E features a built-in GNSS receiver with an internal antenna. For installations where satellite reception is limited, such as when mounted inside a cabin or enclosed area, an optional external GNSS antenna UX-241 is available.

Other Features

- VSWR (Voltage Standing Wave Ratio) detection function notifies antenna issues
- 25 W loud audio, hailer and foghorn functions
- Active noise canceling reduces background noise
- Dualwatch and Tri-watch functions for monitoring Ch. 16 and/or call channel
- Optional flush mount kit for conventional installations
- IPX7 waterproof protection
- AquaQuake™ water draining function
- Priority and normal scan
- Supports 4-digit channels



Dark Mode

VHF Marine Transceiver

IC-M430E



Optional CommandMic™

HM-195GB

SPECIFICATIONS

GENERAL		
Frequency range	TX	156.025 ~ 161.425 MHz
	RX	156.050 ~ 162.000 MHz
	DSC	156.525 MHz
Type of emission	16K0G3E (FM), 16K0G2B (DSC)	
Usable channels	INT, USA channels	
Power supply requirement	12.0 V DC (10.8 ~ 15.6 V DC)	
Current drain (at 12.0 V DC)	TX 25 W output	5.0 A maximum
	RX Max. audio	Less than 1.6 A
		Less than 2.0 A (with HM-195) Less than 4.0 A (with ext SP) Less than 7.0 A (with ext SP, RX hailer, and HM-195)
Operating temperature range	-20°C ~ +60°C	
Antenna impedance	50 Ω	
Audio power output (hailer)	25 W typical	
Dimensions (W x H x D)	202 x 82 x 52.6 mm	
Weight (approx.)	640 g (not including microphone)	

TRANSMITTER

Output power (at 12.0 V DC)	25 W, 1W
Max. frequency deviation	±5 kHz
Frequency error	Less than ±0.5 kHz
Spurious emissions	Less than 0.25 μW (at 25 W)
Adjacent channel power	More than 70 dB
Residual modulation	More than 40 dB

RECEIVER

Sensitivity (at 20 dB SINAD) DSC (1% BER)	-5 dBμ typical -5 dBμ emf typical
Adjacent channel selectivity DSC (1% BER)	More than 70 dB More than 73 dBμ emf
Spurious response DSC (1% BER)	More than 70 dB More than 73 dBμ emf
Intermodulation DSC (1% BER)	More than 68 dB More than 68 dBμ emf
Hum and noise	More than 40 dB
Audio output power (at 10% distortion with 4 Ω)	More than 10 W (external speaker) 16 W typical (RX Hailer)


Measurements made in accordance with EN301 025-2, -3.
All stated specifications are subject to change without notice or obligation.

Applicable IP Rating

INGRESS PROTECTION STANDARD

Water	IPX7 (Waterproof protection)
-------	------------------------------

DIMENSIONS



OPTIONAL ACCESSORIES


COMMANDMIC™



Supplied accessories



SPEAKER MICROPHONE



CONVERSION CABLES



EXTENSION CABLES



AIS TRANSPONDER



HORN SPEAKER



FLUSH MOUNT KIT



GNSS ANTENNA



FRONT PANEL COVER



FLUSH MOUNT GASKET




Some options may not be available in some countries. Please ask your dealer for details.

Supplied accessories:

- DC/AF/DATA connector cable
- Microphone hanger
- Flush mount gasket, MBA-18
- Speaker microphone, HM-205RB
- Mounting bracket kit

ADVANCED CONNECTIONS



Icom and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. COMMANDMIC and AQUAQUAKE are trademarks of Icom Inc. (Japan) in the United States. NMEA 2000 and NMEA 0183 are trademarks of the National Maritime Electronics Association, Inc. All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302

For the latest information, please visit www.icomjapan.com

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom France s.a.s.
www.icomfrance.com/tr/

Icom Canada
www.icomamerica.com

Icom Spain S.L.
www.icomspain.com

Icom (Australia) Pty. Ltd.
www.icom-australia.com

Icom Brazil
www.icomamerica.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom Asia Co., Ltd.
www.icomasia.com